

U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371		ATTORNEY'S DOCKET NUMBER 1454.1125 10/019016
INTERNATIONAL APPLICATION NO. PCT/EP00/05917	INTERNATIONAL FILING DATE 26 June 2000	PRIORITY DATE CLAIMED 25 June 1999
TITLE OF INVENTION METHOD AND DEVICE FOR INPUTTING CONTROL INFORMATION IN COMPUTER SYSTEMS		
APPLICANT(S) FOR DO/EO/US Gerhard BOCK et al.		
Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:		
<ol style="list-style-type: none"> 1. <input checked="" type="checkbox"/> This is a FIRST submission of items concerning a filing under 35 U.S.C. 371. 2. <input checked="" type="checkbox"/> This is an express request to immediately begin national examination procedures (35 U.S.C. 371(f)). 3. <input checked="" type="checkbox"/> The US has been elected by the expiration of 19 months from the priority date (PCT Article 31). 4. <input checked="" type="checkbox"/> A copy of the International Application as filed (35 U.S.C. 371(c)(2)) <ol style="list-style-type: none"> a. <input checked="" type="checkbox"/> is transmitted herewith (required only if not transmitted by the International Bureau). b. <input type="checkbox"/> has been transmitted by the International Bureau. c. <input type="checkbox"/> is not required, as the application was filed in the United States Receiving Office (RO/US). 5. <input checked="" type="checkbox"/> A translation of the International Application into English (35 U.S.C. 371(c)(2)). 6. <input type="checkbox"/> Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3)) <ol style="list-style-type: none"> a. <input type="checkbox"/> are transmitted herewith (required only if not transmitted by the International Bureau). b. <input type="checkbox"/> have been transmitted by the International Bureau. c. <input type="checkbox"/> is not required, as the application was filed in the United States Receiving Office (RO/US). 7. <input type="checkbox"/> A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)). 8. <input type="checkbox"/> An oath or declaration of the inventor (35 U.S.C. 371(c)(4)). 9. <input checked="" type="checkbox"/> A translation of the Annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)). 		
Items 10-15 below concern document(s) or information included:		
<ol style="list-style-type: none"> 10. <input checked="" type="checkbox"/> An Information Disclosure Statement Under 37 CFR 1.97 and 1.98. 11. <input type="checkbox"/> An assignment document for recording. Please mail the recorded assignment document to: <ol style="list-style-type: none"> a. <input type="checkbox"/> the person whose signature, name & address appears at the bottom of this document. b. <input type="checkbox"/> the following: 12. <input checked="" type="checkbox"/> A preliminary amendment. 13. <input checked="" type="checkbox"/> A substitute specification 14. <input type="checkbox"/> A change of power of attorney and/or address letter. 15. <input checked="" type="checkbox"/> Other items or information: <u>First page of published International Application with translation; International Preliminary Examination Report; International Search Report.</u> 		

☒ The U.S. National Fee (35 U.S.C. 371(c)(1)) and other fees as follows:

CLAIMS	(1) FOR	(2) NUMBER FILED	(3) NUMBER EXTRA	(4) RATE	(5) CALCULATIONS
TOTAL CLAIMS		35 -20=	15	x \$ 18.00	270.00
INDEPENDENT CLAIMS		3 -3=	0	x \$ 84.00	0.00
MULTIPLE DEPENDENT CLAIM(S) (if applicable)				+\$280.00	0.00
BASIC NATIONAL FEE (37 CFR 1.492(a)(1)-(4): <input type="checkbox"/> Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO\$1,040 <input checked="" type="checkbox"/> International preliminary examination fee (37 C.F.R. 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO.....\$ 890 <input type="checkbox"/> International preliminary examination fee (37 C.F.R. 1.482) not paid to USPTO but international search fee (37 C.F.R. 1.445(a)(2)) paid to USPTO...\$ 740 <input type="checkbox"/> International preliminary examination fee paid to USPTO (37 CFR 1.482) but all claims did not satisfy provision of PCT Article 33(1)-(4).....\$ 710 <input type="checkbox"/> International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(2) to (4)\$ 100					890.00
Surcharge of \$130 for furnishing the National fee or oath or declaration later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 mos. from the earliest claimed priority date (37 CFR 1.482(e)).					0.00
TOTAL OF ABOVE CALCULATIONS					1160.00
Reduction by 1/2 for filing by small entity, if applicable. Affidavit must be filed also. (Note 37 CFR 1.9, 1.27, 1.28.)					
SUBTOTAL					1160.00
Processing fee of \$130 for furnishing the English Translation later than [] 20 [] 30 mos. from the earliest claimed priority date (37 CFR 1.482(f)).					
TOTAL NATIONAL FEE					1160.00
Fee for recording the enclosed assignment (37 CFR 1.21(h)).					+
TOTAL FEES ENCLOSED					1160.00

- a. ☒ A check in the amount of \$1160.00 to cover the above fees is enclosed.
 b. ☐ Please charge my Deposit Account No. 19-3935 in the Amount of \$ to cover the above fees. A duplicate copy of this sheet is enclosed.
 c. ☒ The Commissioner is hereby authorized to charge any additional fees which may be required, credit any overpayment to Deposit Account No. 19-3935. A duplicate copy of this sheet is enclosed.
- or



21171

PATENT TRADEMARK OFFICE

SUBMITTED BY: STAAS & HALSEY LLP

Type Name	Mark J. Henry	Reg. No.	36,162
Signature		Date	

Docket No.: 1454.1125

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re the Application of:

PCT National Phase of: PCT/EP00/05917

Gerhard BOCK et al.

Serial No.

Group Art Unit: To be assigned

Confirmation No.

Filed: Examiner: To be assigned

For: METHOD AND DEVICE FOR INPUTTING CONTROL INFORMATION IN COMPUTER
SYSTEMS

PRELIMINARY AMENDMENT

Assistant Commissioner for Patents
Washington, D.C. 20231

Sir:

Before examination of the above-identified application, please amend the application as follows:

IN THE ABSTRACT:

Please REPLACE the Abstract originally filed with the enclosed Substitute Abstract attached hereto.

IN THE SPECIFICATION:

Please REPLACE the specification originally filed with the enclosed Substitute Specification.

IN THE CLAIMS:

Please CANCEL claims 1-17.

Please ADD new claims 18-52 in accordance with the following:

18. (NEW) An input device for computer systems, comprising:

a recording unit to serially record image information;

an image evaluation unit to evaluate the recorded image information and determine control information from a relative displacement of the serially recorded image information, the image evaluation unit having an image compression device for generating motion vectors, the control information being a main motion vector of the serially recorded image information

a data processing unit to process the control information in selection information ; and

a display unit to display the selection information .

19. (NEW) The input device as claimed in claim 18, wherein the selection information in a displayed image is at least one of a selection position, a selection field and an entire display area of the display unit .

20. (NEW) The input device as claimed in claim 18, wherein the control information has an x component, wherein the image evaluation unit takes into account a parallel relative displacement of the image information in the x direction.

21. (NEW) The input device as claimed in claim 18, wherein the control information has a y component, wherein the image evaluation unit takes into account a parallel relative displacement of the image information in the y direction.

22. (NEW) The input device as claimed in claim 18, wherein the control information has a z component, wherein the image evaluation unit takes into account a concentric relative displacement of the image information in the x and y directions.

23. (NEW) The input device as claimed in claim 22, wherein the recording unit has a displacement device for creating the parallel and/or concentric relative displacement.

24. (NEW) The input device as claimed in claim 22, wherein the display unit enlarges or reduces the selection information depending on the z component of the control information.

25. (NEW) The input device as claimed in claim 18, wherein the computer system is a

mobile multimedia communication terminal.

26. (NEW) The input device as claimed in claim 25, wherein the recording unit records in the display direction of the display unit.

27. (NEW) The input device as claimed in claim 25, wherein the recording unit records in the opposite direction to the display direction of the display unit.

28. (NEW) The input device as claimed in claim 25, further comprising at least one further recording unit which records in the opposite direction to the display direction of the display unit.

29. (NEW) The input device as claimed in claim 18, wherein the recording unit has a CCD or CMOS sensor camera.

30. (NEW) The input device as claimed in claim 18, further comprising at least one activation element for activating/deactivating the input device.

31. (NEW) The input device as claimed in claim 18, wherein the recording unit is a macro camera system which can record the image information in sharp focus from a very short distance.

32. (NEW) The input device as claimed in claim 18, wherein the recording unit has a pressure sensor for confirming the displayed selection information.

33. (NEW) The input device as claimed in claim 18, wherein the computer system is a mobile videophone.

34. (NEW) The input device as claimed in claim 19, wherein the control information has an x component, wherein the image evaluation unit takes into account a parallel relative displacement of the image information in the x direction.

35. (NEW) The input device as claimed in claim 34, wherein the control information has

a y component, wherein the image evaluation unit takes into account a parallel relative displacement of the image information in the y direction.

36. (NEW) The input device as claimed in claim 35, wherein the control information has a z component, wherein the image evaluation unit takes into account a concentric relative displacement of the image information in the x and y directions.

37. (NEW) The input device as claimed in claim 36, wherein the recording unit has a displacement device for creating the parallel and/or concentric relative displacement.

38. (NEW) The input device as claimed in claim 37, wherein the display unit enlarges or reduces the selection information depending on the z component of the control information.

39. (NEW) The input device as claimed in claim 38, wherein the computer system is a mobile multimedia communication terminal.

40. (NEW) The input device as claimed in claim 39, wherein the recording unit records in the display direction of the display unit.

41. (NEW) The input device as claimed in claim 40, wherein the recording unit records in the opposite direction to the display direction of the display unit.

42. (NEW) The input device as claimed in claim 41, further comprising at least one further recording unit which records in the opposite direction to the display direction of the display unit.

43. (NEW) The input device as claimed in claim 42, wherein the recording unit has a CCD or CMOS sensor camera.

44. (NEW) The input device as claimed in claim 43, further comprising at least one activation element for activating/deactivating the input device.

45. (NEW) The input device as claimed in claim 44, wherein the recording unit is a

macro camera system which can record the image information in sharp focus from a very short distance.

46. (NEW) The input device as claimed in claim 45, wherein the recording unit has a pressure sensor for confirming the displayed selection information.

47. (NEW) The input device as claimed in claim 46, wherein the computer system is a mobile videophone.

48. (NEW) A method for inputting control information in a computer system comprising the steps:

- a) recording first image information;
- b) recording second image information;
- c) determining a relative displacement between the first and second image information; and
- d) generating the control information on the basis of the relative displacement determined,

wherein the determination in step c) is a determination of motion vectors by means of an image compression method; and the generation according to step d) is a generation of control information on the basis of a main motion vector.

49. (NEW) A input device comprising:

- a recorder to record an image at first and second image positions;
- an image evaluation unit to determine the displacement of the image between the first and second positions and to obtain a motion vector from the displacement;
- a display unit to display information; and
- a data processing unit to modify the information displayed on the display unit based on the motion vector.

50. (NEW) An input unit according to claim 49, wherein the data processing unit moves a cursor on the display based on the motion vector.

51. (NEW) An input unit according to claim 49, wherein the data processing unit scrolls

through the information displayed based on the motion vector.

52. (NEW) An input unit according to claim 49, wherein the data processing unit zooms into and out of the information displayed based on the motion vector such that if the second image position is further from the recorder than the first image position, then the data processing unit zooms out of the information displayed, and if the second image position is closer to the recorder than the first image position, then the data processing unit zooms into the information displayed.

REMARKS

This Preliminary Amendment is submitted to improve the form of the specification as originally-filed. A substitute specification and marked-up copy of the original specification are enclosed. No new matter is added to these documents.

It is respectfully requested that this Preliminary Amendment be entered in the above-referenced application.

If any further fees are required in connection with the filing of this Preliminary Amendment, please charge same to our Deposit Account No. 19-3935.

Respectfully submitted,

STAAS & HALSEY LLP

Date: Dec. 26, 2001

By: Mark J. Henry
Mark J. Henry
Registration No. 36,162

700 Eleventh Street, NW, Suite 500
Washington, D.C. 20001
(202) 434-1500

SUBSTITUTE ABSTRACT

The invention relates to an input device for computer systems and to a pertaining method with a recording unit for serially recording image information. An image evaluation unit evaluates a relative displacement of the serially recorded image information, wherein a data processing unit displaces selection information displayed on a display unit on the basis of the determined control information.

- 1 -

Description

Method and device for inputting control information in computer systems

5

The invention relates to a method and a device for inputting control information in computer systems, and in particular to an input device and a pertaining method for operating a mobile multimedia communication terminal (mobile videophone).

10

Mobile communication terminals such as mobile phones for example increasingly have access to "online services". In particular the introduction of the future broadband UMTS mobile communication network will enable high-quality mobile Internet access.

15

Likewise, ultra-small computer systems (such as palmtop computers for example) on which a wide variety of organizer functions (such as address management, diary, task list, etc. for example) are implemented are becoming increasingly important.

20

The operation of these display-driven computer systems requires an input device with which the information displayed on a display unit can be controlled or selected.

Mobile ultra-small computer systems of this type usually have so-called "touch screens" as an input device, wherein the display unit is equipped with a touch-sensitive layer and it is accordingly possible either to input control information or select the displayed information by means of an additional input stylus. The disadvantage of such conventional input devices however is that the additional input stylus has to be accommodated in the device and consequently may get lost. Moreover,

30

- 2 -

user interfaces for these conventional "touch-screen" display units are mechanically not very robust.

So-called conventional "mouse" input devices are also known, wherein a rolling ball is converted into a corresponding electrical signal which is displayed as a pointer symbol or selection information on a display unit. In addition, control keys can be used as an input device for computer systems.

Particularly in the case of ultra-small computer systems however, input devices of this type are not possible because of the greater amount of space required.

As an alternative to the touch-controlled input devices described above, so-called non-contact input devices are known in which, for example, a video camera records a position of an input stylus, evaluates it, and on the basis of the evaluation a pointer symbol or selection information displayed on the display unit is subsequently displaced (e.g. US 5,726,685). Furthermore, a so-called gesture input device is known from the publication US 5,617,312 in which the gestures of a person are recorded by a camera and are subsequently converted into corresponding control signals for controlling a pointer symbol or selection information displayed on the display unit. However, since said input devices are based on relatively complex pattern recognition, they are usually prone to errors and require large amounts of computing power.

Known from the publication EP-A-773 494 forming the preamble of claim 1 is an input device for computer systems having a recording unit for serially recording image information; an image evaluation unit for evaluating the recorded image information and determining

control information; a data processing unit for processing the control information in selection information; and a display unit for displaying the selection information. The image evaluation unit determines the control information from a relative displacement of the serially recorded image information.

A device and a method for controlling a display is also known from publication JP 10 240 436 A, in which a picture or menu displayed on the display is displaced vertically or horizontally respectively depending on a relative movement or displacement of a CCD camera.

In contrast, the object of the invention is to create an input device and a pertaining method for computer systems which is space-saving, cost-effective and reliable.

According to the invention, this object is achieved by the features of claim 1 with respect to the device and by the measures of claim 17 with respect to the method.

Particularly on mobile videophones, the use of an image evaluation unit in particular, which uses an image compression device for generating motion vectors, with the control information being derived from a main motion vector, enables the recording unit already present as well as the associated image compression method to be used simultaneously as an input device.

Respective parallel displacement components of the image information in the x and y directions are preferably used to generate the x and y components of the control information, which enables control of a pointer symbol or

Art. 34

- 3A -

selection information to be realized on a two-dimensional display.
The control information may however also have a z component which
is produced from a concentric displacement of the image
information in the x and y directions, which enables control of a
5 pointer symbol or selection information to be realized on a three-
dimensional or quasi three-dimensional display. In addition, this
enables an intuitive enlargement or reduction of the display
scale. To produce such a concentric displacement of image
information for three-dimensional input, the recording unit can
10 preferably have a zoom function unit.

- > 4

A mobile multimedia communication terminal is preferably used as the computer system, with the recording unit in a mobile videophone being used both for recording a call partner and as an input device. Analogously, a display unit is used both for displaying a call partner and for displaying an Internet page, organizer page, etc. An extremely cost-effective and space-saving realization of the input device is thus achieved. The recording unit comprises in particular a CCD or CMOS sensor camera, which reduces the space requirement still further.

10 The recording unit preferably records image information for input control in the display direction of the display unit, but it can also record image information in the opposite direction. This is particularly advantageous when the input device is provided in a mobile videophone, because when the videophone is placed on a suitable surface, by moving the videophone to and fro, an associated pointer symbol can be correspondingly displaced on the display unit in the same way as with a conventional mouse input device.

20 The recording unit preferably has a macro camera system for recording image information from a very close distance, which enables, for example, an input to be made by placing a finger directly on the recording unit. If the recording unit additionally has a pressure sensor for confirming displayed selection information, then the input device can be operated in the same way as a conventional touch-screen input device.

25 Further advantageous embodiments of the invention are characterized in the subclaims.

The invention is described in greater detail below on the basis of exemplary embodiments and with reference to the drawing, in which:

- Figure 1 shows a schematic diagram of the input device according to the invention;
- Figure 2 shows a schematic diagram of serially recorded image information to illustrate three-dimensional control;
- Figures 3a and 3b show schematic diagrams of a mobile communication terminal having an input device according to a first exemplary embodiment;
- Figure 4 shows a schematic diagram of a mobile communication terminal having an input device according to a second exemplary embodiment; and
- Figures 5a to 5c show schematic diagrams of parts of a mobile communication terminal having an input device according to a third exemplary embodiment.

Figure 1 shows a schematic diagram of an input device according to the invention. In Figure 1, reference numeral 1 denotes a recording unit for serially recording image information, wherein first image information A essentially comprises a landscape with a house, two trees and an industrial building. After swiveling the recording unit 1 in the negative y direction, second image information A' is recorded, which essentially comprises the house, the tree and the industrial building of the first image information A plus an additional fence. Owing to the swiveling of the recording unit 1, the additional tree present in the first image information A is not present in the second image information A'.

An image evaluation unit 3 (AW) serves to evaluate the serially recorded first and second image information A and A', with control information x, y and z being determined. Evaluation of the image evaluation unit 3 is essentially based here on
5 determining a relative displacement between the serially recorded image information, i.e. between the first image information A and the second image information A'. To be more precise, a main displacement vector HV which corresponds to a displacement of the main image components within image information A and A' is
10 determined.

Given the swiveling of the recording unit 1 in the y direction illustrated in Figure 1, when the image information A and A' is evaluated in the evaluation unit 3, the main displacement vector HV is accordingly determined, which
15 essentially represents a displacement in the y direction. The control information in the y direction thus obtained is subsequently processed in a data processing unit 4 (DV) in such a way that a display unit 2 connected to the data processing unit 4 causes a corresponding displacement of selection information P
20 displayed on the display unit 2 to P'. In Figure 1, the selection information displayed on the display unit 2 is a pointer symbol P, which is located in an upper position for a first camera position for recording the first image information A, and moves to a lower position (P') when the recording unit 1 is swiveled to record the
25 second image information A'.

In accordance with Figure 1, therefore, a relative displacement of serially recorded image information can be produced and evaluated by swiveling a recording unit 1, which information produces a displacement of the displayed pointer
30 symbols P to P' on the display unit 2.

The relative displacement is determined here on the basis of the principal structures of image information A and A'. To be more precise, the relative displacement is not determined on the basis of micro displacements, but rather on the basis of macro displacements in the image information A and A'. Macro displacements are understood to be, for example, displacements of the general background of the image information A and A', while micro displacements are displacements of limited image areas as a result of quick and instantaneous movements. Accordingly, a car moving through the landscape illustrated in Figure 1 would not cause a macro displacement, but only a micro displacement of image information which is ignored by the input device.

According to the invention, only macro displacements of the recorded image information are taken into account for the inputting of control information or the control of selection information P and P' displayed on the display unit 2, with a threshold decision element (not shown) setting an absolute magnitude for the macro displacement. Accordingly, a macro displacement is taken into account by the evaluation unit 3 if, for example, at least 90% of the image information recorded by the recording unit 1 exhibits the same or a similar displacement. A parallel displacement in essentially the same x and y direction is interpreted here as the same displacement, while a displacement in the z direction is interpreted as a similar displacement.

Figure 2 shows a schematic diagram for illustrating a relative displacement of image information in a z direction. According to Figure 2, the image information recorded by the recording unit 1 comprises a house which is initially at a distance (image information A) and the same house which, as a result of coming closer in the z direction, is displayed as enlarged by the image information A'.

displacement vectors are not ordered parallel to one another in the x or y direction, but exhibit a concentric displacement direction. Such concentrically oriented displacement vectors can therefore be evaluated by the evaluation unit 3 as control
5 information in the z direction, thus enabling even three-dimensional control of the selection information displayed on the display unit 2, i.e. pointer symbols P and P'. The display unit 2 may also be a three-dimensional display unit here (e.g. holographic display unit).

10 As an alternative to moving the recording unit 1 in the z direction, i.e. moving closer to the object to be recorded, the recording unit 1 can also have an (electronic or mechanical) zoom function unit (not shown) with which it is likewise also possible to perform a concentric displacement of the image information. The
15 recording unit 1 may also have a rotating or swiveling unit (not shown) with which the macro displacements in the x and y directions can be realized.

Figures 3a and 3b show schematic diagrams of a mobile multimedia communication terminal having the input device
20 according to a first exemplary embodiment of the invention. In Figure 3a, MM denotes a mobile multimedia communication terminal, as may be realized for example in the form of a mobile videophone with Internet access. In addition to the usual function units, the mobile multimedia communication terminal MM essentially has a
25 recording unit 1, a display unit 2 and an activation button T for activating/deactivating the input device. In the case of an Internet access, the enlarged Internet page IS (web page) is displayed on the display unit 2 for example, with a pointer symbol P being displayed as selection information at the position I. To
30 move the pointer symbol P from position I to position II, according to Figure 3b a user can, for example, move the mobile multimedia communication terminal MM downward in front of his face, with the result that, instead of image information A at position I, the image information A' at position II is now
35 recorded by the recording unit 1. The resulting macro displacements are detected by the evaluation unit 3, as described above, and are processed by the data processing unit 4 in such a way that the display unit 2 now displays the pointer P' at

position II of the displayed Internet page IS. A displacement of the pointer symbol P showing the selection information to P' is thus achieved in this way by displacing the recording unit 1 relative to the recorded background.

5 As was already described above, it is also possible to perform a swiveling instead of the vertical displacement of the mobile multimedia communication terminal from a position I to a position II, which enables the pointer symbol P to be displaced in the same manner to position II for the pointer symbol P'.

10 Mobile multimedia communication terminals, as illustrated by way of example in Figures 3a and 3b, are especially advantageous if they are equipped as mobile videophones. Mobile videophones already have a large display unit 2 as well as a recording unit 1 for recording image information. Moreover, such
15 mobile videophones already have an image compression device as image evaluation unit 3 for compressing the recorded image information. The algorithms used for image compression detect a movement in the image information A and A', with the movement of the total image information being calculated in such a way to
20 produce a total or main motion vector which is equivalent to the movement or displacement of the mobile multimedia communication terminal MM or the associated image information A and A' respectively. This total or main motion vector, which can be readily calculated during image compression, can now be processed
25 as

control information with corresponding x, y and z components, and displace the selection information, i.e. the pointer symbols P or P', accordingly. Since the compression algorithms used are
30 essentially already present in a mobile videophone, no additional costs are incurred. To switch over or activate/deactivate the input device, the mobile videophone or mobile multimedia communication terminal MM requires only an activation button T.

Figure 4 shows a schematic diagram of a mobile multimedia
35 communication terminal having an input device according to a second exemplary embodiment. In Figure 4 the same reference symbols denote the same or corresponding components as in

Figures 3a and 3b, so a detailed description is dispensed with below.

On a mobile multimedia communication terminal MM having an input device according to the second exemplary embodiment, the display unit 2 does not display the complete Internet page IS, but only a selected section F. This way of displaying of information, for example from the Internet or from another application, has the advantage that the information on the displayed page IS is more readily legible for the user.

According to the present invention, the input device now has intuitive control of the information page IS to be displayed. To be more precise, a user need only displace the mobile multimedia communication terminal with the recording unit 1 in the x and y directions in order to reach the respective sections of the information page IS, so that the information page IS can be read intuitively (i.e. by displacing a viewing window) without using any further keys or input media.

In addition, a displacement in the z direction, i.e. a forward/backward movement of the mobile multimedia communication terminal MM, can enlarge or reduce the size of the selected section F, which enables intuitive use comparable to the use of a magnifying glass.

According to Figures 3 and 4, the recording unit 1 is located on the front of the mobile multimedia communication terminal MM. It can however also be located on the rear of the terminal, or a second recording unit may be arranged on the rear of the mobile multimedia communication terminal MM. Given suitable realization of the optics, i.e. the ability to focus the recording unit 1 even at a very short distance, the mobile multimedia communication terminal MM can also be placed rear down on a suitably structured surface and the whole unit can be displaced in the same way as a mouse. The recording unit located on the rear detects here, as described above, the relative movement or relative displacement of the recorded image information (structured surface) and determines from it the corresponding control information for controlling the selection information, i.e. a pointer symbol P or a display section F of the information page IS. This results in the input device being particularly easy to operate, since it essentially corresponds to a conventional mouse input device. In this case the mobile multimedia communication terminal preferably has the selection buttons (not shown) known from conventional mouse input devices.

Figures 5a to 5c show enlarged partial views of a mobile multimedia communication terminal MM having an input device according to a third exemplary embodiment. In Figures 5a to 5c, the same reference symbols denote the same components as in Figures 1 to 4, so a detailed description is dispensed with below.

According to Figures 5a to 5c, the input device according to the third exemplary embodiment can be used in the same way as a conventional so-called "touch-pad" input device. In Figure 5a, reference numeral 1 again denotes a recording unit 1, but one which is a special macro camera system. To be more precise, the recording unit 1 according to Figures 5a to 5c is able to record very fine structures in the immediate vicinity of the camera, by

means of which, for example, the finger lines of a finger placed directly on the recording unit are recorded in sharp focus.

According to Figures 5a to 5c, the display unit 2 shows a telephone directory list with a plurality of names and corresponding phone numbers. The telephone directory list displayed on the display unit 2 thus corresponds to an information page IS, with the selection information being represented neither by a pointer symbol P for indicating a selection position, nor by a display area F, but by a predetermined selection field B in the form of a, for example, colored bar. To control the input, or to select the name Meier with phone number 345678, the user then places his finger on the recording unit 1, with the input device activated by means of the activation button T (not shown). According to Figure 5b, the finger lines are now recorded as image information A, and the user moves his finger downward to displace the bar B. Figure 5c shows here a partial view of the mobile multimedia communication terminal MM, with the finger shown at a lower position. The recording unit 1 accordingly detected a displacement of the recorded image information A A' on the basis of the finger lines and evaluated this as a vertical displacement downward. The evaluation unit 3 accordingly outputs corresponding control information to the data processing unit 4, which results in the bar B being displaced downward on the display unit 2 and now highlighting the desired name Meier with phone number 345678.

To select the desired name, according to the third exemplary embodiment the input device can also have a pressure sensor for confirming the displayed selection information, i.e. the name highlighted by the bar B, which dispenses with the need for further fixed keys or so-called menu-driven "soft keys".

Given suitable dimensioning of the recording unit 1 and the evaluation unit 3, in this way it is also possible to make an input in a way known from conventional "touch pads" and/or "touch screens" for example. The integration of a pressure sensor in the recording unit 1 further reduces the space required for the input device and enhances ease of operation. In comparison with conventional "touch pads" in particular, with the input device according to the third exemplary embodiment, it is not the main focus of a surface area which is determined, but rather the exact

position or movement of the finger is tracked on the basis of the lines present on it. The precision of this input device is therefore much greater than that of conventional input devices. With the input device according to the third exemplary embodiment, 5 therefore, essentially a relative macro displacement of the recorded image information is also used to control selection information.

A CCD or CMOS sensor camera is preferably used as the recording unit 1. The recording unit 1 is located here either on 10 the front or on the rear of an input or computer system respectively, but it is not limited thereto and may also be arranged at a different position and be moved around, for example by means of mirrors, in the same or opposite direction to the display direction of the display unit 2.

15

The invention was described above with reference to a mobile multimedia communication terminal. It is however not limited thereto, and likewise encompasses ultra-small computer systems without a communication link, such as palmtop computers
5 for example. Likewise, the present invention may also be used on corded telecommunication terminals and other computer systems.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221

Patent Claims

1. An input device for computer systems having:
a recording unit (1) for serially recording image information (A,
5 A');
an image evaluation unit (3) for evaluating the recorded image
information (A, A') and determining control information (x, y, z);
a data processing unit (4) for processing the control information
(x, y, z) in selection information (P; B; F); and
10 a display unit (2) for displaying the selection information (P; B;
F), in which
the image evaluation unit (3) determines the control information
(x, y, z) from a relative displacement of the serially recorded
image information (A, A'),
15 characterized in that the image evaluation unit (3) has an image
compression device for generating motion vectors, wherein the
control information is a main motion vector (x, y, z) of the
serially recorded image information (A, A').
2. The input device as claimed in claim 1, characterized in
20 that the selection information in a displayed image (IS) is a
selection position (P), a selection field (B) and/or an entire
display area (F) of the display unit (2).
3. The input device as claimed in claim 1 or 2,
characterized in that the control information has an x component,
25 wherein the image evaluation unit (3) essentially takes into
account a parallel relative displacement of the image information
(A, A') in the x direction.
4. The input device as claimed in one of claims 1 to 3,
characterized in that the

- 2 -

control information has a y component, wherein the image evaluation unit (3) essentially takes into account a parallel relative displacement of the image information (A, A') in the y direction.

5 5. The input device as claimed in one of claims 1 to 4, characterized in that the control information has a z component, wherein the image evaluation unit (3) essentially takes into account a concentric relative displacement of the image information (A, A') in the x and y directions.

10 6. The input device as claimed in claim 5, characterized in that the recording unit (1) has a displacement device for creating the parallel and/or concentric relative displacement.

7. The input device as claimed in claim 5 or 6, characterized in that the display unit (2) enlarges or reduces the selection information (F) depending on the z component of the control information.

8. The input device as claimed in one of claims 1 to 7, characterized in that the computer system is a mobile multimedia communication terminal (MM).

20 9. The input device as claimed in claim 8, characterized in that the recording unit (1) records in the display direction of the display unit (2).

10. The input device as claimed in one of claims 8 or 9, characterized in that the recording unit (1) records in the opposite direction to the display direction of the display unit (2).

11. The input device as claimed in claim 8 or 9, characterized by at least one further recording unit which records in the opposite direction to the display direction of the display unit (2).

5 12. The input device as claimed in one of claims 1 to 11, characterized in that the recording unit has a CCD or CMOS sensor camera.

13. The input device as claimed in one of claims 1 to 12, characterized by at least one activation element (T) for
10 activating/deactivating the input device.

14. The input device as claimed in one of claims 1 to 13, characterized in that the recording unit (1) is a macro camera system which can record the image information (A, A') in sharp focus from a very short distance.

15 15. The input device as claimed in one of claims 1 to 14, characterized in that the recording unit (1) has a pressure sensor for confirming the displayed selection information (P, B, F).

16. The input device as claimed in one of claims 1 to 15, characterized in that the computer system is a mobile videophone.

20 17. A method for inputting control information in a computer system comprising the steps:

- a) recording first image information (A);
- b) recording second image information (A');
- c) determining a relative displacement between the first and
25 second image information; and

d) generating the control information (x, y, z) on
the basis of the relative displacement determined,
characterized in that the determination in step c) is a
determination of motion vectors by means of an image compression
5 method; and the generation according to step d) is a generation of
control information (x, y, z) on the basis of a main motion
vector.

Method and device for inputting control information in computer systems

Figure 1

Figure 1

1/4

FIG 1






FIG 2








FIG 5A




FIG 5B





FIG 5C



SUBSTITUTE SPECIFICATION

TITLE OF THE INVENTION

METHOD AND DEVICE FOR INPUTTING CONTROL INFORMATION IN COMPUTER SYSTEMS

[0001] This application is based on and hereby claims priority to PCT Application No. PCT/EP00/05917 filed on June 26, 2000, and European Application No. 99112287.0 filed June 25, 1999 in Europe, the contents of which are hereby incorporated by reference.

BACKGROUND OF THE INVENTION

[0002] The invention relates to a method and a device for inputting control information in computer systems, and in particular to an input device and a pertaining method for operating a mobile multimedia communication terminal (mobile videophone).

[0003] Mobile communication terminals such as mobile phones for example increasingly have access to "online services". In particular the introduction of the future broadband UMTS mobile communication network will enable high-quality mobile Internet access.

[0004] Likewise, ultra-small computer systems (such as palmtop computers for example) on which a wide variety of organizer functions (such as address management, diary, task list, etc. for example) are implemented are becoming increasingly important.

[0005] The operation of these display-driven computer systems requires an input device with which the information displayed on a display unit can be controlled or selected.

[0006] Mobile ultra-small computer systems of this type usually have so-called "touch screens" as an input device, wherein the display unit is equipped with a touch-sensitive layer and it is accordingly possible either to input control information or select the displayed information by an additional input stylus. The disadvantage of such input devices however is that the additional input stylus has to be accommodated in the device and consequently may get lost. Moreover, user interfaces for these "touch-screen" display units are mechanically not very robust.

[0007] So-called "mouse" input devices are also known, wherein a rolling ball is converted into a corresponding electrical signal which is displayed as a pointer symbol or selection information on a display unit. In addition, control keys can be used as an input device for computer systems.

[0008] Particularly in the case of ultra-small computer systems however, input devices of this type are not possible because of the greater amount of space required.

[0009] As an alternative to the touch-controlled input devices described above, so-called non-contact input devices are known in which, for example, a video camera records a position of an input stylus, evaluates it, and on the basis of the evaluation a pointer symbol or selection information displayed on the display unit is subsequently displaced (e.g. US 5,726,685). Furthermore, a so-called gesture input device is known from the publication US 5,617,312 in which the gestures of a person are recorded by a camera and are subsequently converted into corresponding control signals for controlling a pointer symbol or selection information displayed on the display unit. However, since said input devices are based on relatively complex pattern recognition, they are usually prone to errors and require large amounts of computing power.

[0010] Known from the publication EP-A-773 494 is an input device for computer systems having a recording unit for serially recording image information; an image evaluation unit for evaluating the recorded image information and determining control information; a data processing unit for processing the control information in selection information; and a display unit for displaying the selection information. The image evaluation unit determines the control information from a relative displacement of the serially recorded image information.

[0011] A device and a method for controlling a display is also known from publication JP 10 240 436 A, in which a picture or menu displayed on the display is displaced vertically or horizontally respectively depending on a relative movement or displacement of a CCD camera.

SUMMARY OF THE INVENTION

[0012] In contrast, one possible object of the invention is to create an input device and a pertaining method for computer systems which is space-saving, cost-effective and reliable.

[0013] Particularly on mobile videophones, the use of an image evaluation unit in particular, which uses an image compression device for generating motion vectors, with the control information being derived from a main motion vector, enables the recording unit already present as well as the associated image compression method to be used simultaneously as an input device.

[0014] Respective parallel displacement components of the image information in the x and y directions are preferably used to generate the x and y components of the control information, which enables control of a pointer symbol or selection information to be realized on a two-

dimensional display. The control information may however also have a z component which is produced from a concentric displacement of the image information in the x and y directions, which enables control of a pointer symbol or selection information to be realized on a three-dimensional or quasi three-dimensional display. In addition, this enables an intuitive enlargement or reduction of the display scale. To produce such a concentric displacement of image information for three-dimensional input, the recording unit can preferably have a zoom function unit.

[0015] A mobile multimedia communication terminal is preferably used as the computer system, with the recording unit in a mobile videophone being used both for recording a call partner and as an input device. Analogously, a display unit is used both for displaying a call partner and for displaying an Internet page, organizer page, etc. An extremely cost-effective and space-saving realization of the input device is thus achieved. The recording unit comprises in particular a CCD or CMOS sensor camera, which reduces the space requirement still further.

[0016] The recording unit preferably records image information for input control in the display direction of the display unit, but it can also record image information in the opposite direction. This is particularly advantageous when the input device is provided in a mobile videophone, because when the videophone is placed on a suitable surface, by moving the videophone to and fro, an associated pointer symbol can be correspondingly displaced on the display unit in the same way as with a mouse input device.

[0017] The recording unit preferably has a macro camera system for recording image information from a very close distance, which enables, for example, an input to be made by placing a finger directly on the recording unit. If the recording unit additionally has a pressure sensor for confirming displayed selection information, then the input device can be operated in the same way as a touch-screen input device.

BRIEF DESCRIPTION OF THE DRAWINGS

[0018] These and other objects and advantages of the present invention will become more apparent and more readily appreciated from the following description of the preferred embodiments, taken in conjunction with the accompanying drawings of which:

Fig. 1 shows a schematic diagram of the input device according to one aspect of the invention;

Fig. 2 shows a schematic diagram of serially recorded image information to illustrate three-dimensional control;

Figs. 3a and 3b show schematic diagrams of a mobile communication terminal having an input device according to a first exemplary embodiment;

Fig. 4 shows a schematic diagram of a mobile communication terminal having an input device according to a second exemplary embodiment; and

Figs. 5a to 5c show schematic diagrams of parts of a mobile communication terminal having an input device according to a third exemplary embodiment.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

[0019] Reference will now be made in detail to the preferred embodiments of the present invention, examples of which are illustrated in the accompanying drawings, wherein like reference numerals refer to like elements throughout.

[0020] Fig. 1 shows a schematic diagram of an input device. In Fig. 1, reference numeral 1 denotes a recording unit for serially recording image information, wherein first image information A essentially comprises a landscape with a house, two trees and an industrial building. After swiveling the recording unit 1 in the negative y direction, second image information A' is recorded, which essentially comprises the house, the tree and the industrial building of the first image information A plus an additional fence. Owing to the swiveling of the recording unit 1, the additional tree present in the first image information A is not present in the second image information A'.

[0021] An image evaluation unit 3 (AW) serves to evaluate the serially recorded first and second image information A and A', with control information x, y and z being determined. Evaluation of the image evaluation unit 3 is essentially based here on determining a relative displacement between the serially recorded image information, i.e. between the first image information A and the second image information A'. To be more precise, a main displacement vector HV which corresponds to a displacement of the main image components within image information A and A' is determined.

[0022] Given the swiveling of the recording unit 1 in the y direction illustrated in Fig. 1, when the image information A and A' is evaluated in the evaluation unit 3, the main displacement vector HV is accordingly determined, which essentially represents a displacement in the y direction. The control information in the y direction thus obtained is subsequently processed in a data processing unit 4 (DV) in such a way that a display unit 2 connected to the data

processing unit 4 causes a corresponding displacement of selection information P displayed on the display unit 2 to P'. In Fig. 1, the selection information displayed on the display unit 2 is a pointer symbol P, which is located in an upper position for a first camera position for recording the first image information A, and moves to a lower position (P') when the recording unit 1 is swiveled to record the second image information A'.

[0023] In accordance with Fig. 1, therefore, a relative displacement of serially recorded image information can be produced and evaluated by swiveling a recording unit 1, which information produces a displacement of the displayed pointer symbols P to P' on the display unit 2.

[0024] The relative displacement is determined here on the basis of the principal structures of image information A and A'. To be more precise, the relative displacement is not determined on the basis of micro displacements, but rather on the basis of macro displacements in the image information A and A'. Macro displacements are understood to be, for example, displacements of the general background of the image information A and A', while micro displacements are displacements of limited image areas as a result of quick and instantaneous movements.

Accordingly, a car moving through the landscape illustrated in Fig. 1 would not cause a macro displacement, but only a micro displacement of image information which is ignored by the input device.

[0025] Only macro displacements of the recorded image information are taken into account for the inputting of control information or the control of selection information P and P' displayed on the display unit 2, with a threshold decision element (not shown) setting an absolute magnitude for the macro displacement. Accordingly, a macro displacement is taken into account by the evaluation unit 3 if, for example, at least 90% of the image information recorded by the recording unit 1 exhibits the same or a similar displacement. A parallel displacement in essentially the same x and y direction is interpreted here as the same displacement, while a displacement in the z direction is interpreted as a similar displacement.

[0026] Fig. 2 shows a schematic diagram for illustrating a relative displacement of image information in a z direction. According to Fig. 2, the image information recorded by the recording unit 1 comprises a house which is initially at a distance (image information A) and the same house which, as a result of coming closer in the z direction, is displayed as enlarged by the image information A'.

[0027] Accordingly, given a displacement in the z direction, the displacement vectors are not ordered parallel to one another in the x or y direction, but exhibit a concentric displacement

direction. Such concentrically oriented displacement vectors can therefore be evaluated by the evaluation unit 3 as control information in the z direction, thus enabling even three-dimensional control of the selection information displayed on the display unit 2, i.e. pointer symbols P and P'. The display unit 2 may also be a three-dimensional display unit here (e.g. holographic display unit).

[0028] As an alternative to moving the recording unit 1 in the z direction, i.e. moving closer to the object to be recorded, the recording unit 1 can also have an (electronic or mechanical) zoom function unit (not shown) with which it is likewise also possible to perform a concentric displacement of the image information. The recording unit 1 may also have a rotating or swiveling unit (not shown) with which the macro displacements in the x and y directions can be realized.

[0029] Figs. 3a and 3b show schematic diagrams of a mobile multimedia communication terminal having the input device according to a first exemplary embodiment of the invention. In Fig. 3a, MM denotes a mobile multimedia communication terminal, as may be realized for example in the form of a mobile videophone with Internet access. In addition to the usual function units, the mobile multimedia communication terminal MM essentially has a recording unit 1, a display unit 2 and an activation button T for activating/deactivating the input device. In the case of an Internet access, the enlarged Internet page IS (web page) is displayed on the display unit 2 for example, with a pointer symbol P being displayed as selection information at the position I. To move the pointer symbol P from position I to position II, according to Fig. 3b a user can, for example, move the mobile multimedia communication terminal MM downward in front of his face, with the result that, instead of image information A at position I, the image information A' at position II is now recorded by the recording unit 1. The resulting macro displacements are detected by the evaluation unit 3, as described above, and are processed by the data processing unit 4 in such a way that the display unit 2 now displays the pointer P' at position II of the displayed Internet page IS. A displacement of the pointer symbol P showing the selection information to P' is thus achieved in this way by displacing the recording unit 1 relative to the recorded background.

[0030] As was already described above, it is also possible to perform a swiveling instead of the vertical displacement of the mobile multimedia communication terminal from a position I to a position II, which enables the pointer symbol P to be displaced in the same manner to position II for the pointer symbol P'.

[0031] Mobile multimedia communication terminals, as illustrated by way of example in Figs. 3a and 3b, are especially advantageous if they are equipped as mobile videophones. Mobile videophones already have a large display unit 2 as well as a recording unit 1 for recording image information. Moreover, such mobile videophones already have an image compression device as image evaluation unit 3 for compressing the recorded image information. The algorithms used for image compression detect a movement in the image information A and A', with the movement of the total image information being calculated in such a way to produce a total or main motion vector which is equivalent to the movement or displacement of the mobile multimedia communication terminal MM or the associated image information A and A' respectively. This total or main motion vector, which can be readily calculated during image compression, can now be processed as control information with corresponding x, y and z components, and displace the selection information, i.e. the pointer symbols P or P', accordingly. Since the compression algorithms used are essentially already present in a mobile videophone, no additional costs are incurred. To switch over or activate/deactivate the input device, the mobile videophone or mobile multimedia communication terminal MM requires only an activation button T.

[0032] Fig. 4 shows a schematic diagram of a mobile multimedia communication terminal having an input device according to a second exemplary embodiment. In Fig. 4 the same reference symbols denote the same or corresponding components as in Figs. 3a and 3b, so a detailed description is dispensed with below.

[0033] On a mobile multimedia communication terminal MM having an input device according to the second exemplary embodiment, the display unit 2 does not display the complete Internet page IS, but only a selected section F. This way of displaying of information, for example from the Internet or from another application, has the advantage that the information on the displayed page IS is more readily legible for the user.

[0034] According to the second exemplary embodiment, the input device now has intuitive control of the information page IS to be displayed. To be more precise, a user need only displace the mobile multimedia communication terminal with the recording unit 1 in the x and y directions in order to reach the respective sections of the information page IS, so that the information page IS can be read intuitively (i.e. by displacing a viewing window) without using any further keys or input media.

[0035] In addition, a displacement in the z direction, i.e. a forward/backward movement of the mobile multimedia communication terminal MM, can enlarge or reduce the size of the selected section F, which enables intuitive use comparable to the use of a magnifying glass.

[0036] According to Figs. 3 and 4, the recording unit 1 is located on the front of the mobile multimedia communication terminal MM. It can however also be located on the rear of the terminal, or a second recording unit may be arranged on the rear of the mobile multimedia communication terminal MM. Given suitable realization of the optics, i.e. the ability to focus the recording unit 1 even at a very short distance, the mobile multimedia communication terminal MM can also be placed rear down on a suitably structured surface and the whole unit can be displaced in the same way as a mouse. The recording unit located on the rear detects here, as described above, the relative movement or relative displacement of the recorded image information (structured surface) and determines from it the corresponding control information for controlling the selection information, i.e. a pointer symbol P or a display section F of the information page IS. This results in the input device being particularly easy to operate, since it essentially corresponds to a mouse input device. In this case the mobile multimedia communication terminal preferably has the selection buttons (not shown) known from mouse input devices.

[0037] Figs. 5a to 5c show enlarged partial views of a mobile multimedia communication terminal MM having an input device according to a third exemplary embodiment. In Figs. 5a to 5c, the same reference symbols denote the same components as in Figs. 1 to 4, so a detailed description is dispensed with below.

[0038] According to Figs. 5a to 5c, the input device according to the third exemplary embodiment can be used in the same way as a so-called "touch-pad" input device. In Fig. 5a, reference numeral 1 again denotes a recording unit 1, but one which is a special macro camera system. To be more precise, the recording unit 1 according to Figs. 5a to 5c is able to record very fine structures in the immediate vicinity of the camera, by which, for example, the finger lines of a finger placed directly on the recording unit are recorded in sharp focus.

[0039] According to Figs. 5a to 5c, the display unit 2 shows a telephone directory list with a plurality of names and corresponding phone numbers. The telephone directory list displayed on the display unit 2 thus corresponds to an information page IS, with the selection information being represented neither by a pointer symbol P for indicating a selection position, nor by a display area F, but by a predetermined selection field B in the form of a, for example, colored

bar. To control the input, or to select the name Meier with phone number 345678, the user then places his finger on the recording unit 1, with the input device activated by the activation button T (not shown). According to Fig. 5b, the finger lines are now recorded as image information A, and the user moves his finger downward to displace the bar B. Fig. 5c shows here a partial view of the mobile multimedia communication terminal MM, with the finger shown at a lower position. The recording unit 1 accordingly detected a displacement of the recorded image information $A \rightarrow A'$ on the basis of the finger lines and evaluated this as a vertical displacement downward. The evaluation unit 3 accordingly outputs corresponding control information to the data processing unit 4, which results in the bar B being displaced downward on the display unit 2 and now highlighting the desired name Meier with phone number 345678.

[0040] To select the desired name, according to the third exemplary embodiment the input device can also have a pressure sensor for confirming the displayed selection information, i.e. the name highlighted by the bar B, which dispenses with the need for further fixed keys or so-called menu-driven "soft keys".

[0041] Given suitable dimensioning of the recording unit 1 and the evaluation unit 3, in this way it is also possible to make an input in a way known from "touch pads" and/or "touch screens" for example. The integration of a pressure sensor in the recording unit 1 further reduces the space required for the input device and enhances ease of operation. In comparison with known "touch pads" in particular, with the input device according to the third exemplary embodiment, it is not the main focus of a surface area which is determined, but rather the exact position or movement of the finger is tracked on the basis of the lines present on it. The precision of this input device is therefore much greater than that of known input devices. With the input device according to the third exemplary embodiment, therefore, essentially a relative macro displacement of the recorded image information is also used to control selection information.

[0042] A CCD or CMOS sensor camera is preferably used as the recording unit 1. The recording unit 1 is located here either on the front or on the rear of an input or computer system respectively, but it is not limited thereto and may also be arranged at a different position and be moved around, for example by mirrors, in the same or opposite direction to the display direction of the display unit 2.

[0043] The invention was described above with reference to a mobile multimedia communication terminal. It is however not limited thereto, and likewise encompasses ultra-small computer systems without a communication link, such as palmtop computers for example.

[0044] The invention has been described in detail with particular reference to preferred embodiments thereof and examples, but it will be understood that variations and modifications can be effected within the spirit and scope of the invention.

Declaration and Power of Attorney For Patent Application

Erklärung Für Patentanmeldungen Mit Vollmacht

German Language Declaration

Als nachstehend benannter Erfinder erkläre ich hiermit an Eides Statt:

As a below named inventor, I hereby declare that:

dass mein Wohnsitz, meine Postanschrift, und meine Staatsangehörigkeit den im Nachstehenden nach meinem Namen aufgeführten Angaben entsprechen,

My residence, post office address and citizenship are as stated below next to my name,

dass ich, nach bestem Wissen der ursprüngliche, erste und alleinige Erfinder (falls nachstehend nur ein Name angegeben ist) oder ein ursprünglicher, erster und Miterfinder (falls nachstehend mehrere Namen aufgeführt sind) des Gegenstandes bin, für den dieser Antrag gestellt wird und für den ein Patent beantragt wird für die Erfindung mit dem Titel:

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

Vorrichtung und Verfahren zur Eingabe
von Steuerinformationen in
Computersysteme

Method and device for inputting control
information in computer systems

deren Beschreibung

the specification of which

(zutreffendes ankreuzen)

☐ hier beigefügt ist.

☒ am 26.06.2000 als

PCT internationale Anmeldung

PCT Anmeldungsnummer PCT/EP00/05917

eingereicht wurde und am _____

abgeändert wurde (falls tatsächlich abgeändert).

(check one)

☐ is attached hereto.

☒ was filed on 26.06.2000 as

PCT international application

PCT Application No. PCT/EP00/05917

and was amended on _____

(if applicable)

Ich bestätige hiermit, dass ich den Inhalt der obigen Patentanmeldung einschliesslich der Ansprüche durchgesehen und verstanden habe, die eventuell durch einen Zusatzantrag wie oben erwähnt abgeändert wurde.

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims as amended by any amendment referred to above.

Ich erkenne meine Pflicht zur Offenbarung irgendwelcher Informationen, die für die Prüfung der vorliegenden Anmeldung in Einklang mit Absatz 37, Bundesgesetzbuch, Paragraph 1.56(a) von Wichtigkeit sind, an.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56(a).

Ich beanspruche hiermit ausländische Prioritätsvorteile gemäss Abschnitt 35 der Zivilprozessordnung der Vereinigten Staaten, Paragraph 119 aller unten angegebenen Auslandsanmeldungen für ein Patent oder eine Erfindersurkunde, und habe auch alle Auslandsanmeldungen für ein Patent oder eine Erfindersurkunde nachstehend gekennzeichnet, die ein Anmeldedatum haben, das vor dem Anmeldedatum der Anmeldung liegt, für die Priorität beansprucht wird.

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

German Language Declaration

Prior foreign applications

Priorität beansprucht

Priority Claimed

99112287.0

(Number)
(Nummer)

EP

(Country)
(Land)

25.06.1999

(Day Month Year Filed)
(Tag Monat Jahr eingereicht)

☒

Yes
Ja

☐

No
Nein

(Number)
(Nummer)

(Country)
(Land)

(Day Month Year Filed)
(Tag Monat Jahr eingereicht)

☐

Yes
Ja

☐

No
Nein

(Number)
(Nummer)

(Country)
(Land)

(Day Month Year Filed)
(Tag Monat Jahr eingereicht)

☐

Yes
Ja

☐

No
Nein

Ich beanspruche hiermit gemäss Absatz 35 der Zivilprozessordnung der Vereinigten Staaten, Paragraph 120, den Vorzug aller unten aufgeführten Anmeldungen und falls der Gegenstand aus jedem Anspruch dieser Anmeldung nicht in einer früheren amerikanischen Patentanmeldung laut dem ersten Paragraphen des Absatzes 35 der Zivilprozessordnung der Vereinigten Staaten, Paragraph 122 offenbart ist, erkenne ich gemäss Absatz 37, Bundesgesetzbuch, Paragraph 1.56(a) meine Pflicht zur Offenbarung von Informationen an, die zwischen dem Anmeldedatum der früheren Anmeldung und dem nationalen oder PCT internationalen Anmeldedatum dieser Anmeldung bekannt geworden sind.

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §122, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application.

PCT/EP00/05917

(Application Serial No.)
(Anmeldeseriennummer)

26.06.2000

(Filing Date D, M, Y)
(Anmeldedatum T, M, J)

anhängig

(Status)
(patentiert, anhängig,
aufgegeben)

pending

(Status)
(patented, pending,
abandoned)

(Application Serial No.)
(Anmeldeseriennummer)

(Filing Date D,M,Y)
(Anmeldedatum T, M; J)

(Status)
(patentiert, anhängig,
aufgeben)

(Status)
(patented, pending,
abandoned)

Ich erkläre hiermit, dass alle von mir in der vorliegenden Erklärung gemachten Angaben nach meinem besten Wissen und Gewissen der vollen Wahrheit entsprechen, und dass ich diese eidesstattliche Erklärung in Kenntnis dessen abgebe, dass wissentlich und vorsätzlich falsche Angaben gemäss Paragraph 1001, Absatz 18 der Zivilprozessordnung der Vereinigten Staaten von Amerika mit Geldstrafe belegt und/oder Gefängnis bestraft werden koennen, und dass derartig wissentlich und vorsätzlich falsche Angaben die Gültigkeit der vorliegenden Patentanmeldung oder eines darauf erteilten Patentes gefährden können.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true, and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

German Language Declaration

VERTRETUNGSVOLLMACHT: Als benannter Erfinder beauftrage ich hiermit den nachstehend benannten Patentanwalt (oder die nachstehend benannten Patentanwälte) und/oder Patent-Agenten mit der Verfolgung der vorliegenden Patentanmeldung sowie mit der Abwicklung aller damit verbundenen Geschäfte vor dem Patent- und Warenzeichenamt: (Name und Registrationsnummer anführen)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (list name and registration number)

And I hereby appoint

Customer No. 21171

Telefongespräche bitte richten an:
(Name und Telefonnummer)

Direct Telephone Calls to: (name and telephone number)

Ext. _____

Postanschrift:

Send Correspondence to:


Staas & Halsey LLP
700 Eleventh Street NW, Suite 500 20001 Washington, DC
Telephone: (001) 202 434 1500 and Facsimile (001) 202 434 1501
or

Customer No. 21171

<p>Voller Name des einzigen oder ursprünglichen Erfinders: GERHARD BOCK</p> <p>Unterschrift des Erfinders Datum 21.11.01</p> <p>Wohnsitz KRAILLING, DEUTSCHLAND</p> <p>Staatsangehörigkeit DE</p> <p>Postanschrift FRUEHLINGSTR. 19 82152 KRAILLING</p>	<p>Full name of sole or first inventor: GERHARD BOCK</p> <p>Inventor's signature Date </p> <p>Residence KRAILLING, GERMANY DEX</p> <p>Citizenship DE</p> <p>Post Office Address FRUEHLINGSTR. 19 82152 KRAILLING</p>
<p>Voller Name des zweiten Miterfinders (falls zutreffend): CHRISTINE KOCOUREK</p> <p>Unterschrift des Erfinders Datum 5.1.02</p> <p>Wohnsitz MUENCHEN, DEUTSCHLAND</p> <p>Staatsangehörigkeit DE</p> <p>Postanschrift TRAUNREUTER STR. 30 81549 MUENCHEN</p>	<p>Full name of second joint inventor, if any: CHRISTINE KOCOUREK</p> <p>Second Inventor's signature Date </p> <p>Residence MUENCHEN, GERMANY DEX</p> <p>Citizenship DE</p> <p>Post Office Address TRAUNREUTER STR. 30 81549 MUENCHEN</p>

(Bitte entsprechende Informationen und Unterschriften im Falle von dritten und weiteren Miterfindern angeben).

(Supply similar information and signature for third and subsequent joint inventors).

Voller Name des dritten Miterfinders: FRITZ SEYTTER		Full name of third joint inventor: FRITZ SEYTTER	
Unterschrift des Erfinders 	Datum 18.12.01	Inventor's signature	Date
Wohnsitz MUENCHEN, DEUTSCHLAND		Residence MUENCHEN, GERMANY DEX	
Staatsangehörigkeit DE		Citizenship DE	
Postanschrift ASAMSTR. 12 C		Post Office Address ASAMSTR. 12 C	
81541 MUENCHEN		81541 MUENCHEN	
Voller Name des vierten Miterfinders:		Full name of fourth joint inventor:	
Unterschrift des Erfinders	Datum	Inventor's signature	Date
Wohnsitz		Residence	
Staatsangehörigkeit		Citizenship	
Postanschrift		Post Office Address	
Voller Name des fünften Miterfinders:		Full name of fifth joint inventor:	
Unterschrift des Erfinders	Datum	Inventor's signature	Date
Wohnsitz		Residence	
Staatsangehörigkeit		Citizenship	
Postanschrift		Post Office Address	
Voller Name des sechsten Miterfinders:		Full name of sixth joint inventor:	
Unterschrift des Erfinders	Datum	Inventor's signature	Date
Wohnsitz		Residence	
Staatsangehörigkeit		Citizenship	
Postanschrift		Post Office Address	

(Bitte entsprechende Informationen und Unterschriften im Falle von dritten und weiteren Miterfindern angeben).

(Supply similar information and signature for third and subsequent joint inventors).